MATERIAL SAFETY DATA SHEET

Titan Industrial Chemicals, LLC PO Box 635 Grover, MO 63040-0635

GENERAL INFORMATION NUMBER: (636) 273-9033 REVISION DATE: September 18, 2003

DATE OF ISSUE: April 29, 2008

I - Product Identification

Grow No More PRODUCT CODE: 0320

CHEMICAL FORMULATION: Solvent based non-selective residual herbicide.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0 HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

	Values reported as TWA unless noted.						
	APPROX	OSHA	ACGIH	EPA 40 CFR:			
SUBSTANCE	<u>%</u>	<u>PEL</u>	$\underline{\mathbf{TLV}}$	<u>302</u>	<u>355</u>	<u>372</u>	CAS#
Isoctyl ester of 2,4-Dichlorophenxyacetic acid	1.09	10 mg/m^3	N/E	Y	N	Y	1928-43-4
Bromacil	0.98	N/E	10 mg/m^3	N	N	Y	314-40-9
Aliphatic Hydrocarbons	80.0-90.0	N/E	N/E	N	N	N	68476-31-3
2-Butoxyethanol	10.0-20.0	25 ppm (skin)	25 ppm (skin)	N	N	Y	111-76-2

Key: PEL: Permissible Exposure Limit N/A: Not Applicable TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D **SPECIFIC GRAVITY (WATER = 1):** 0.875

VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): N/D

VAPOR DENSITY (AIR = 1): N/D **EVAPORATION RATE (WATER = 1):** > 1.0

SOLUBILITY IN WATER: Insoluble **pH:** N/A

APPEARANCE AND ODOR: Reddish brown liquid; fuel oil odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 145 (TEST METHOD): Closed cup FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/D LOWER: N/D

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus. Minimize amount of water used to fight fire as run-off may cause pollution. **UNUSUAL FIRE AND EXPLOSION HAZARD:** Solvent vapors may cause flashback.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers.

CONDITIONS TO AVOID: Excess heat and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X EYE CONTACT: X SKIN CONTACT: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None. EFFECTS OF OVEREXPOSURE

IF IN EYES: Severe irritation, redness, tearing and blurred vision.

IF ON SKIN: Redness, dryness and irritation with prolonged or repeated exposure.

IF SWALLOWED: Gastrointestinal irritation, nausea, cramps, vomiting.

IF INHALED: Irritation to upper respiratory tract, weakness, headache, nausea, unconsciousness.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove and launder all affected clothing. Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting.

IF INHALED: Remove person to fresh air. If breathing has stopped, give artificial respiration. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill. Ventilate area and remove all sources of ignition. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal. WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION LOCAL: Recommended MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant. **EYE PROTECTION:** Safety goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Eyewash station, protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat and open flame.

Keep container tightly closed when not in use. Do not contaminate water, foodstuffs or feed by storage or disposal.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: None

DOT CLASS: None DOT ID NUMBER: None DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: September 18, 2003 Prepared by: PMR DATE OF ISSUE: April 29, 2008

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Titan Industrial Chemicals, LLC assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.