SAFETY DATA SHEET

Issue Date October 27,2015 Revision Date Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name EASY STRIP N/R

Other means of identification

Product Code 40700

Details of the supplier of the safety data sheet

Company Name TITAN INDUSTRIAL CHEMICALS, LLC

P.O. BOX 635 GROVER, MO. 63040 636-273-9033

Emergency telephone number

Emergency Telephone INFOTRAC 1-800-535-5053

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Dermal	Not classified
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity-single exposure (respiratory)	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

May be harmful if swallowed Causes severe skin burns and eye damage Causes serious eye damage Suspected of causing cancer May cause respiratory irritation



Appearance Clear Physical state Liquid Odor Glycol ether

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Unknown Acute Toxicity

0.02933% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
2-Propanol	67-63-0	1-5	*
Monoethanolamine	141-43-5	10-20	*
2-butoxyethanol	111-76-2	10-20	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret. The exact identities of other ingredients has also been withheld as Trade Secret. However, they do not contribute to the identified hazards of the product and will be divulged to proper authorities in an emergency.

4. FIRST AID MEASURES

First aid measures

General advice Immediate medical attention is required.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes.

Eye contact Immediate medical attention is required. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected

area.

Inhalation Remove to fresh air. Call a physician or poison control center immediately. If not breathing,

give artificial respiration. If breathing is difficult, give oxygen.

Ingestion Immediate medical attention is required. Do NOT induce vomiting. Drink plenty of water.

Never give anything by mouth to an unconscious person. Remove from exposure, lie down. Clean mouth with water and drink afterwards plenty of water. Call a physician or poison

control center immediately.

Self-protection of the first aiderUse personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Any additional important symptoms and effects are described in Section 11: Toxicology

Information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat

symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautionsDo not allow into any sewer, on the ground or into any body of water. Should not be

released into the environment. Prevent further leakage or spillage if safe to do so. Prevent

product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take

up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains. Dam up. After cleaning, flush away traces

with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed

systems.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in

properly labeled containers.

Incompatible materials Incompatible with strong acids and bases. Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure GuidelinesThis product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Propanol	opanol STEL: 400 ppm TWA: 400 ppm		IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
Monoethanolamine	STEL: 6 ppm	TWA: 3 ppm	IDLH: 30 ppm
141-43-5	TWA: 3 ppm	TWA: 6 mg/m ³	TWA: 3 ppm
		(vacated) TWA: 3 ppm	TWA: 8 mg/m ³
		(vacated) TWA: 8 mg/m ³	STEL: 6 ppm
		(vacated) STEL: 6 ppm	STEL: 15 mg/m ³
		(vacated) STEL: 15 mg/m ³	
2-butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m ³	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³
		(vacated) TWA: 120 mg/m ³	
		(vacated) S*	
		S*	
Diethanolamine	TWA: 1 mg/m ³ inhalable fraction	(vacated) TWA: 3 ppm	TWA: 3 ppm
111-42-2	and vapor	(vacated) TWA: 15 mg/m ³	TWA: 15 mg/m ³
	S*		

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers, Eyewash stations & Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a face shield if splashing hazard

exists.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Take off all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When using do not eat, drink or smoke. Keep away from food, drink and animal feeding stuffs. Regular cleaning of equipment, work area

and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Appearance Clear

Color Colorless to Light Amber

Odor Glycol ether

Odor threshold No Information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH 12.0 - 13.0 **Specific Gravity** .973

Viscosity <25 cP @ 25°C

Melting point/freezing point No Information available

Flash point Above 200°F

Boiling point / boiling range

Evaporation rate

No Information available
No Information available

Flammability (solid, gas)
Flammability Limits in Air

Upper flammability limit:

Lower flammability limit:

Vapor pressure

Vapor density

No Information available
No Information available
No Information available

Water solubility Complete

Partition coefficientNo Information availableAutoignition temperatureNo Information availableDecomposition temperatureNo Information available

Other Information

Density Lbs/Gal 8.106 VOC Content (%) 5.2

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation No data available. Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes. Causes severe eye damage.

Skin Contact Avoid contact with skin. Causes severe irritation and or burns.

Ingestion May be harmful if swallowed. Do not taste or swallow. Not an expected route of exposure.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Propanol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1000 mg/kg (Rabbit)	-
2-butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h

Information on toxicological effects

Symptoms No Information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo Information available.
No Information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Propanol 67-63-0	-	Group 3	-	Х
2-butoxyethanol 111-76-2	А3	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No Information available.
No Information available.

Chronic toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects. May cause adverse effects on the bone marrow and

blood-forming system. May cause adverse liver effects.

Target organ effects Blood, Central nervous system, EYES, hematopoietic system, Kidney, Liver, Respiratory

system, Skin.

Aspiration hazard No Information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.02933% of the mixture consists of ingredient(s) of unknown toxicity

12. ECOLOGICAL INFORMATION

Ecotoxicity

2.70933% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Propanol	1000: 96 h Desmodesmus	9640: 96 h Pimephales promelas	13299: 48 h Daphnia magna mg/L
67-63-0	subspicatus mg/L EC50 1000: 72 h	mg/L LC50 flow-through 11130: 96	EC50
	Desmodesmus subspicatus mg/L	h Pimephales promelas mg/L LC50	
	EC50	static 1400000: 96 h Lepomis	
		macrochirus μg/L LC50	
Monoethanolamine	15: 72 h Desmodesmus subspicatus	227: 96 h Pimephales promelas	65: 48 h Daphnia magna mg/L
141-43-5	mg/L EC50	mg/L LC50 flow-through 3684: 96 h	EC50
		Brachydanio rerio mg/L LC50 static	
		300 - 1000: 96 h Lepomis	
		macrochirus mg/L LC50 static 114 -	
		196: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 200: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through	
2-butoxyethanol	-	1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static 2950: 96 h	EC50 1698 - 1940: 24 h Daphnia
		Lepomis macrochirus mg/L LC50	magna mg/L EC50
Diethanolamine	7.8: 72 h Desmodesmus	4460 - 4980: 96 h Pimephales	55: 48 h Daphnia magna mg/L
111-42-2	subspicatus mg/L EC50 2.1 - 2.3: 96	promelas mg/L LC50 flow-through	EC50
	h Pseudokirchneriella subcapitata	1200 - 1580: 96 h Pimephales	
	mg/L EC50	promelas mg/L LC50 static 600 -	
		1000: 96 h Lepomis macrochirus	
		mg/L LC50 static	

Persistence and degradability

No Information available.

Bioaccumulation

No Information available.

Chemical Name	Partition coefficient
2-Propanol 67-63-0	0.05
Monoethanolamine 141-43-5	-1.91
2-butoxyethanol 111-76-2	0.81

Other adverse effects No Information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status

2-Propanol	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

The basic description below is specific to the container size. This information is provided for at a glance DOT information. Please refer to the container and/or shipping papers for the appropriate shipping description before tendering this material for shipment. For additional information, please contact the distributor listed in section 1 of this SDS.

DOT

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
2-Propanol - 67-63-0	1.0	
SARA 311/312 Hazard Categories		
Acute health hazard	Yes	
Chronic Health Hazard	Yes	
Fire hazard	No	
Sudden release of pressure hazard	No	

No

CWA (Clean Water Act)

Reactive Hazard

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N/A				

CERCLA

This material, as supplied, contains no substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
N/A			

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Diethanolamine - 111-42-2	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania

2-Propanol 67-63-0	Х	X	X
Monoethanolamine 141-43-5	Х	X	X
2-butoxyethanol 111-76-2	X	X	X
Diethanolamine 111-42-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION

NFPA Health hazards 3 Flammability 0 Instability 0 Physical and Chemical Properties Yes

HMIS Health hazards 3 Flammability 0 Physical hazards 0 Personal protection X

Issue Date October 27, 2015

Revision Date Revision Note

No Information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet